



**METALTECNICA**  
Italian catering equipment

## Exhaust hood



Air inlet unit, motor with 1 speed, cap. mc/h 10000, prevalence hs20, cm 165x125x110h - RTA100/I

### **Dimension:**

Length: 165.0 mm

Depth: 125.0 mm  
 Height: 110.0 mm  
 Weight: 191.0 kg  
 Volume: 2.63 mq  
 Packaging length: 175.0 mm  
 Packaging depth: 135.0 mm  
 Packaging height: 120.0 mm  
 Packaging weight: 206.0 kg  
 Packaging volume: 2.84 mq

### Options:

|                                                                                                         |
|---------------------------------------------------------------------------------------------------------|
| <b>Model:</b>                                                                                           |
| <b>RTA120/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 12000, prevalence hs20, cm 165x140x120h |
| <b>RTA150/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 15000, prevalence hs20, cm 165x175x120h |
| <b>RTA180/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 18000, prevalence hs20, cm 165x175x120h |
| <b>RTA20/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 2000, prevalence hs15, cm 110x70x65h     |
| <b>RTA30/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 3000, prevalence hs15, cm 120x80x65h     |
| <b>RTA40/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 4000, prevalence hs15, cm 135x85x75h     |
| <b>RTA50/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 5000, prevalence hs20, cm 135x95x85h     |
| <b>RTA60/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 6000, prevalence hs20, cm 145x105x85h    |
| <b>RTA70/1</b> - Air inlet unit, motor with 1 speed, cap. mc/h 7000, prevalence hs20, cm 150x110x100h   |

**RTA80/1** - Air inlet unit, motor with 1 speed, cap. mc/h 8000, prevalence hs20, cm  
150x115x105h

**RTA90/1** - Air inlet unit, motor with 1 speed, cap. mc/h 9000, prevalence hs20, cm  
165x120x110h