



**METALTECNICA**  
Italian catering equipment

## Exhaust hood



Air inlet unit, motor with 1 speed, cap. mc/h 6000, prevalence hs20, cm  
145x105x85h - RTA60/ILPV

### **Dimension:**

Length: 145.0 mm

Depth: 105.0 mm  
Height: 85.0 mm  
Weight: 112.0 kg  
Volume: 1.0 m³  
Packaging length: 155.0 mm  
Packaging depth: 115.0 mm  
Packaging height: 95.0 mm  
Packaging weight: 127.0 kg  
Packaging volume: 1.69 m³

### Options:

| Model:                                                                                                     |
|------------------------------------------------------------------------------------------------------------|
| <b>RTA100/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 10000, prevalence hs20, cm 165x125x110h |
| <b>RTA120/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 12000, prevalence hs20, cm 165x140x120h |
| <b>RTA150/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 15000, prevalence hs20, cm 165x175x120h |
| <b>RTA180/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 18000, prevalence hs20, cm 165x175x120h |
| <b>RTA20/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 2000, prevalence hs15, cm 110x70x65h     |
| <b>RTA30/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 3000, prevalence hs15, cm 120x80x65h     |
| <b>RTA40/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 4000, prevalence hs15, cm 135x85x75h     |
| <b>RTA50/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 5000, prevalence hs20, cm 135x95x85h     |
| <b>RTA70/1LPV</b> - Air inlet unit, motor with 1 speed, cap. mc/h 7000, prevalence hs20, cm 150x110x100h   |

**RTA80/1LPV** - Air inlet unit, motor with 1 speed, cap. mc/h 8000, prevalence hs20, cm  
150x115x105h

**RTA90/1LPV** - Air inlet unit, motor with 1 speed, cap. mc/h 9000, prevalence hs20, cm  
165x120x110h