



**METALTECNICA**  
Italian catering equipment

## Exhaust hood



Air inlet unit, motor with 2 speeds, cap. mc/h 3000, prevalence hs15, cm  
120x80x65h - RTA30LPV

### **Dimension:**

Length: 120.0 mm

Depth: 80.0 mm  
 Height: 65.0 mm  
 Weight: 89.0 kg  
 Volume: 0.46 mq  
 Packaging length: 130.0 mm  
 Packaging depth: 90.0 mm  
 Packaging height: 75.0 mm  
 Packaging weight: 104.0 kg  
 Packaging volume: 0.88 mq

### Options:

|                                                                                                           |
|-----------------------------------------------------------------------------------------------------------|
| <b>Model:</b>                                                                                             |
| <b>RTA100LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 10000, prevalence hs20, cm 165x125x110h |
| <b>RTA120LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 12000, prevalence hs20, cm 165x140x120h |
| <b>RTA150LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 15000, prevalence hs20, cm 165x175x120h |
| <b>RTA180LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 18000, prevalence hs20, cm 165x175x120h |
| <b>RTA20LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 2000, prevalence hs15, cm 110x70x65h     |
| <b>RTA40LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 4000, prevalence hs15, cm 135x85x75h     |
| <b>RTA50LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 5000, prevalence hs20, cm 135x95x85h     |
| <b>RTA60/LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 6000, prevalence hs20, cm 145x105x85h   |
| <b>RTA70LPV</b> - Air inlet unit, motor with 2 speeds, cap. mc/h 7000, prevalence hs20, cm 150x110x100h   |

**RTA80LPV** - Air inlet unit, motor with 2 speeds, cap. mc/h 8000, prevalence hs20, cm  
150x115x105h

**RTA90LPV** - Air inlet unit, motor with 2 speeds, cap. mc/h 9000, prevalence hs20, cm  
165x120x110h