



METALTECNICA  
Italian catering equipment

---

## Trolley

---



Refrigerated trolley (GN not included), Carrying frame and shelves made in solid wood. Pressed no-drops basin made in stainless steel 18/10 AISI 304. Dome made in transparent plexiglass. Hermetic circuit refrigerating system, consisting of HP 1/8 500 W - 230 V, single-phase compressor unit. The temperature is controlled by a digital thermostat approx.  $-5^{\circ}+10^{\circ}$  C. 4 swivelling wheels covered with casing  $\varnothing$  100 mm. Refrigerated trolley, rectangular dome, capacity 3 GN 1/2 h 200 mm;

### Dimension:

Length: 1050.0 mm

Depth: 450.0 mm

Height: 1150.0 mm

Weight: 80.0 kg

Volume: 0.54 m<sup>3</sup>

Packaging length: 1050.0 mm

Packaging depth: 750.0 mm

Packaging height: 1350.0 mm

Packaging weight: 95.0 kg

Packaging volume: 1.06 m<sup>3</sup>

### Options:

#### Model:

**0118.C** - Refrigerated trolley (GN not included), Carrying frame and shelves made in solid wood. Pressed no-drops basin made in stainless steel 18/10 AISI 304. Dome made in transparent plexiglass. Hermetic circuit refrigerating system, consisting of HP 1/8 500 W - 230 V, single-phase compressor unit. The temperature is controlled by a digital thermostat approx. -5°+10° C. 4 swivelling wheels covered with casing Ø 100 mm. Refrigerated trolley, semi-cylindrical dome, capacity 3 GN 1/2 h 200 mm; dim. mm 1050x450x1150 h

**0131.C** - Refrigerated trolley (GN not included), Carrying frame and shelves made in solid wood. Pressed no-drops basin made in stainless steel 18/10 AISI 304. Dome made in transparent plexiglass. Hermetic circuit refrigerating system, consisting of HP 1/8 500 W - 230 V, single-phase compressor unit. The temperature is controlled by a digital thermostat approx. -5°+10° C. 4 swivelling wheels covered with casing Ø 100 mm. Refrigerated trolley, semi-cylindrical dome, capacity 3 GN 1/1 h 200 mm; dim. mm 1200x640x1150 h

**0131.L** - Refrigerated trolley (GN not included), Carrying frame and shelves made in

solid wood. Pressed no-drops basin made in stainless steel 18/10 AISI 304. Dome made in transparent plexiglass. Hermetic circuit refrigerating system, consisting of HP 1/8 500 W - 230 V, single-phase compressor unit. The temperature is controlled by a digital thermostat approx.  $-5^{\circ}+10^{\circ}$  C. 4 swivelling wheels covered with casing  $\varnothing$  100 mm. Refrigerated trolley, rectangular dome, capacity 3 GN 1/1 h 200 mm; dim. mm 1200x640x1150 h