



METALTECNICA
Italian catering equipment

Trolley



Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 2 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways,

pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2GN1/1 h 200, 2 heated and ventilated cabinet, mm 850x700x900 h - 039.AB/2

Dimension:

Length: 850.0 mm

Depth: 700.0 mm

Height: 900.0 mm

Weight: 71.0 kg

Volume: 0.54 mq

Packaging length: 1050.0 mm

Packaging depth: 750.0 mm

Packaging height: 1100.0 mm

Packaging weight: 81.0 kg

Packaging volume: 0.87 mq

Options:

Model:

039.AB/0 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 2 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2GN1/1 h 200, 2 neutral cabinet, mm 850x700x900 h

039.AB/1 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated

basins with rounded corners, for 2 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2GN1/1 h 200, 1 neutral cabinet and 1 heated and ventilated cabinet, mm 850x700x900 h

039.AC/0 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 3 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3GN1/1 h 200, 3 neutral cabinet, mm 1200x700x900 h

039.AC/1 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 3 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3GN1/1 h 200, 2 neutral cabinet and 1 heated and ventilated cabinet, mm 1200x700x900 h

039.AC/2 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 3 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3GN1/1 h 200, 1 neutral cabinet and 2 heated and ventilated cabinet, mm 1200x700x900 h

039.AC/3 - Heated bain-marie trolley separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Dry/bainmarie heating, temperature

controlled by digital thermostat 30° - 90° C° 230 V 50/60 Hz. Deep-drawn separated basins with rounded corners, for 3 GN1/1 H 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle, Under compartments with hiding tilting doors, with 5 deep-drawn slideways, pitch 55 mm, capacity 2 GN1/1 h 100 mm + 1 GN1/1 h 40 mm, each cabinet. 4 grey not marking rubber wheels diam. 125 mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3GN1/1 h 200, 3 heated and ventilated cabinet, mm 1200x700x900 h