



METALTECNICA
Italian catering equipment

Trolley



Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with

hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 1 neutral cabinet and 1 heated and ventilated cabinet, mm 850x700x1100 h - 040.A/1

Dimension:

Length: 850.0 mm

Depth: 700.0 mm

Height: 1100.0 mm

Weight: 84.0 kg

Volume: 0.65 mq

Packaging length: 1050.0 mm

Packaging depth: 750.0 mm

Packaging height: 1300.0 mm

Packaging weight: 94.0 kg

Packaging volume: 1.02 mq

Options:

Model:

040.A/0 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 2 neutral cabinet, mm 850x700x1100 h

040.A/2 - Heated bain-marie trolley unique basin with sliding lids (GN not included),

structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap. 2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 2 heated and ventilated cabinet, mm 850x700x1100 h

041.A/0 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap. 2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 3 neutral cabinet, mm 1200x700x1100 h

041.A/1 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap. 2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 2 neutral cabinet and 1 heated and ventilated cabinet, mm 1200x700x1100 h

041.A/2 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap. 2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 1 neutral cabinet and 2 heated and ventilated cabinet, mm 1200x700x1100 h

041.A/3 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap. 2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 3 heated and ventilated cabinet, mm 1200x700x1100 h