



METALTECNICA
Italian catering equipment

Trolley



Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 5000x500x900 h - 690.R50

Dimension:

Length: 5000.0 mm

Depth: 500.0 mm

Height: 900.0 mm

Weight: 130.0 kg

Volume: 2.25 mq

Packaging length: 5100.0 mm

Packaging depth: 600.0 mm

Packaging height: 1100.0 mm

Packaging weight: 150.0 kg

Packaging volume: 3.37 mq

Options:

Model:

690.R100 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 10000x500x900 h

690.R30 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 3000x500x900 h

690.R40 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When

wider than 4 m it will leave disassembled. Dim. mm 4000x500x900 h

690.R60 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 6000x500x900 h

690.R70 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 7000x500x900 h

690.R80 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 8000x500x900 h

690.R90 - Conveyor belt. Structure in stainless steel AISI 304 18/10. Control display with the switches "START" - "GO" - with light and detector of ride ending. STOP and two EMERGENCY buttons. Speed control 2.5 - 12 m/min. Structure and legs with adjustable feet. Polyurethane carpet with white PVC cover, with humidity-proof and adapt to food contact. Carpet width mm 300. Under-drawer for dirt collection. 400V 50Hz 3PH+E. Side electric plugs and control panel 220V IP65 (non included). When wider than 4 m it will leave disassembled. Dim. mm 9000x500x900 h