

Trolley



Heated dishes distributor with 1 fixed column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Static version with mechanical thermostat +30° - +90°C, 0.9 kW - 230 V 50/60 Hz. Lids included. Capacity 50-60 dishes, diam 18/28 900 W. Dim. mm 600x480x1060 h - CSP/1S

Dimension:

Length: 600.0 mm Depth: 480.0 mm Height: 1060.0 mm Weight: 35.0 kg Volume: 0.31 mq Packaging length: 750.0 mm Packaging depth: 750.0 mm Packaging height: 1260.0 mm Packaging weight: 45.0 kg Packaging volume: 0.71 mq

Options:

Model:

CSG/IC - Heated dishes distributor with 1 adjustable column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Digital thermostatic regulation +30° - +90°C, 0.9 kW - 230 V 50/60 Hz. Lids included. Capacity 50-60 dishes, diam 28/32 900 W. Dim. mm 650x530x1060 h

CSG/1S - Heated dishes distributor with 1 fixed column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Static version with mechanical thermostat +30° - +90°C, 0.9 kW - 230 V 50/60 Hz. Lids included. Capacity 50-60 dishes, diam 28/32 900 W. Dim. mm 650x530x1060 h

CSL/IC - Heated dishes distributor with 1 fixed column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Digital thermostatic regulation +30° - +90°C, 0.9 kW - 230 V 50/60 Hz. Lids included. Capacity 50-60 dishes, diam 16/21, 900 W. Dim. mm 600x480x1060 h

CSL/1S - Heated dishes distributor with 1 fixed column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Static version with mechanical thermostat +30° - +90°C, 0.9 kW - 230 V 50/60 Hz. Lids included. Capacity 50-60 dishes, diam 16/21 900 W. Dim. mm 600x480x1060 h

CSP/IC - Heated dishes distributor with 1 adjustable column. Entirely made in 18/10 stainless steel with 2 fixed wheels and 2 swivelling diam. 125 mm with brake and corner bumper. Digital thermostatic regulation +30° - +90°C, 0.9 kW - 230 V 50/60 Hz.