

Trolley



Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with

Metaltecnica © Page 1 of 4

hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 2 neutral cabinet, mm 850x700x1100 h - 040.A/0

Dimension:

Length: 850.0 mm Depth: 700.0 mm Height: 1100.0 mm Weight: 83.0 kg Volume: 0.65 mg

Packaging length: 1050.0 mm Packaging depth: 750.0 mm Packaging height: 1300.0 mm Packaging weight: 93.0 kg Packaging volume: 1.02 mq

Options:

Model:

040.A/1 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AlSI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 1 neutral cabinet and 1 heated and ventilated cabinet, mm 850x700x1100 h

040.A/2 - Heated bain-marie trolley unique basin with sliding lids (GN not included),

Metaltecnica © Page 2 of 4

structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 2 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 2GN1/1 h 200, 2 heated and ventilated cabinet, mm 850x700x1100 h

O41.A/O - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GNI/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGNI/1 h 100mm + 1xGNI/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GNI/1 h 200, 3 neutral cabinet, mm 1200x700x1100 h

O41.A/1 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 2 neutral cabinet and 1 heated and ventilated cabinet, mm 1200x700x1100 h

O41.A/2 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GNI/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGNI/1 h 100mm + 1xGNI/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GNI/1 h 200, 1 neutral cabinet and 2 heated and ventilated cabinet, mm 1200x700x1100 h

Metaltecnica © Page 3 of 4

041.A/3 - Heated bain-marie trolley unique basin with sliding lids (GN not included), structure completely made in stainless steel 18/10 AISI 304 dry/bainmarie heating, Temperature controlled by digital thermostat 30°-90° 230V 50/60Hz. Insulated lids are opening up to 180°. Printed unique basin with rounded corners, for 3 GN1/1 H 200mm, anti-drop board, insulated double wall, Spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm cap.2xGN1/1 h 100mm + 1xGN1/1 h 40mm each cabinet. 4 grey not marking rubber wheels. diam 125mm (2 fixed, 2 swivelling with brake). Black PVC perimeter bumpers. Capacity 3GN1/1 h 200, 3 heated and ventilated cabinet, mm 1200x700x1100 h

Metaltecnica © Page 4 of 4