



METALTECNICA  
Italian catering equipment

## Trolley



Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 2 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1

GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2 GN1/1 H 200, with 2 neutral cabinet mm 850x700x900 h - 038.AB/0

#### Dimension:

Length: 850.0 mm

Depth: 700.0 mm

Height: 900.0 mm

Weight: 65.0 kg

Volume: 0.54 mq

Packaging length: 1050.0 mm

Packaging depth: 750.0 mm

Packaging height: 1100.0 mm

Packaging weight: 75.0 kg

Packaging volume: 0.87 mq

#### Options:

##### Model:

**038.AB/1** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 2 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2 GN1/1 H 200, with 1 neutral cabinet and 1 heated and ventilated cabinet mm 850x700x900 h

**038.AB/2** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 2 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5

printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 2 GN1/1 H 200, with 2 heated and ventilated cabinet mm 850x700x900 h

**038.AC/0** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 3 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3 GN1/1 H 200, with 3 neutral cabinet mm 1200x700x900 h

**038.AC/1** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 3 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3 GN1/1 H 200, with 2 neutral cabinet and 1 heated and ventilated cabinet mm 1200x700x900 h

**038.AC/2** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 3 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake). Black PVC perimeter bumpers. Cap. 3 GN1/1 H 200, with 1 neutral cabinet and 2 heated and ventilated cabinet mm 1200x700x900 h

**038.AC/3** - Heated bain-marie trolley unique basin, structure completely made in stainless steel 18/10 AISI 304, dry/bainmarie heating, temperature controlled by digital thermostat 30° - 90° C°. Printed unique basin with rounded corners, for 3 GN1/1 h 200, anti-drop board, insulated double wall, spiral electrical wire with CE plug and hooker for the plug, ergonomic push handle. Under compartments with hiding tilting doors, with 5 printed slideways, pitch 55mm, capacity 2 GN1/1 h 100 mm + 1 GN/ h 40 mm each cabinet. Four grey not marking rubber wheels diam. 125mm (2 fixed, 2 with brake).

Black PVC perimeter bumpers. Cap. 3 GN1/1 H 200, with 3 heated and ventilated cabinet mm 1200x700x900 h