



METALTECNICA
Italian catering equipment

Trolley



Bain-marie heated trolley with lid and without undershelf, carrying frame made in stainless steel 18/10 AISI 304. Stainless steel basin with grid for containers support. Electric water-bath heating, 2000W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Bain-marie heated trolley 2000W mm 1200x640x900 h - 013.A

Dimension:

Length: 1200.0 mm

Depth: 640.0 mm

Height: 900.0 mm

Weight: 48.0 kg

Volume: 0.69 m³

Packaging length: 1250.0 mm

Packaging depth: 750.0 mm

Packaging height: 1100.0 mm

Packaging weight: 58.0 kg

Packaging volume: 1.03 m³

Options:**Model:**

014.A - Bain-marie heated trolley with lid and without undershelf, carrying frame made in stainless steel 18/10 AISI 304. Stainless steel basin with grid for containers support. Electric water-bath heating, 2000W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Bain-marie heated trolley 2000W mm 1500x640x900 h

026.AA - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 1 GN 1/1 h 200 (15-20 meals) mm 710x450x900 h

026.AA/M - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a mechanical thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 1 GN 1/1 h 200 (15-20 meals) mm 710x450x900 h

026.AB - Bain-marie heated trolley for distribution of meals (GN not included).

Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 12GN 1/1 h 200 (30-40 meals) mm 850x640x900 h

026.AB/M - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a mechanical thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 2GN 1/1 h 200 (30-40 meals) mm 850x640x900 h

026.AC - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 3GN 1/1 h 200 (50-60 meals) mm 1200x640x900 h

026.AC/M - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a mechanical thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 3GN 1/1 h 200 (50-60 meals) mm 1200x640x900 h

026.AD - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a digital thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 4GN 1/1 h 200 (60 - 80 meals) mm 1500x640x900 h

026.AD/M - Bain-marie heated trolley for distribution of meals (GN not included). Welded frame made in stainless steel 18/10 AISI 304. Double-wall basin. Bain-marie electric water-bath heating 2000 W - 230 V. Temperature controlled by a mechanical thermostat 30° - 90° C°. Spiral cable with "Schuko" plug. 4 grey not marking, rubber swivelling wheels, 2 with brake Ø 125 mm. Trolley capacity 4GN 1/1 h 200 (60 - 80 meals) mm 1500x640x900 h