



METALTECNICA
Italian catering equipment

Trolley



Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not

marking rubber fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC. Capacity 3 GN1/1 H 200, heated and ventilated cabinet, mm 1200x640x900 h - 026.AC/AR

Dimension:

Length: 1200.0 mm

Depth: 640.0 mm

Height: 900.0 mm

Weight: 69.0 kg

Volume: 0.69 mq

Packaging length: 1250.0 mm

Packaging depth: 750.0 mm

Packaging height: 1200.0 mm

Packaging weight: 79.0 kg

Packaging volume: 1.13 mq

Options:

Model:

026.AB/A - Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not marking rubber fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC. Capacity 2 GN1/1 H 200, neutral cabinet, mm 850x640x900 h

026.AB/AR - Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not marking rubber

fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC.
Capacity 2 GN1/1 H 200, heated and ventilated cabinet, mm 850x640x900 h

026.AC/A - Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not marking rubber fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC.
Capacity 3 GN1/1 H 200, neutral cabinet, mm 1200x640x900 h

026.AD/A - Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not marking rubber fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC.
Capacity 4 GN1/1 H 200, neutral cabinet, mm 1500x640x900 h

026.AD/AR - Heated trolley with unique deep-drawn basin (GN not included). Frame made in stainless steel 18/10 AISI 304. Deep-drawn basin for GN h 200 mm with rounded angles, double and insulated wall, neutral lower compartment closed by swing doors. Temperature controlled by digital thermostat 30° - 90° C°. Spiral cable with CE plug and socket hooks; push handle. Heating by electrical resistance external to the basin functioning bain-marie and dry ways 230 V 50/60 Hz. 2 grey not marking rubber fixed wheels Ø 125 mm and 2 with brake. 4 rubber bumpers made in black PVC.
Capacity 4 GN1/1 H 200, heated and ventilated cabinet, mm 1500x640x900 h