



METALTECNICA  
Italian catering equipment

## Trolley



Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE

plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 4 GN1/1, Basin divided in 4 compartments with 4 temp., neutral swing cabinet, mm 1580x700x900 h - 036.AC

#### Dimension:

Length: 1580.0 mm

Depth: 700.0 mm

Height: 900.0 mm

Weight: 75.0 kg

Volume: 1.0 mq

Packaging length: 1650.0 mm

Packaging depth: 750.0 mm

Packaging height: 1100.0 mm

Packaging weight: 85.0 kg

Packaging volume: 1.36 mq

#### Options:

##### Model:

**032.AC** - Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 2 GN1/1, Basin divided in 2 compartments with 2 temp., neutral swing cabinet, mm 850x700x900 h

**033.AC** - Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment

closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 3 GN1/1, Basin divided in 3 compartments with 3 temp., neutral swing cabinet, mm 1200x700x900 h

**034.AC** - Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 2 GN1/1, Basin divided in 2 compartments with 2 temp., heated and ventilated swing cabinet, mm 850x700x900 h

**035.AC** - Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 3 GN1/1, Basin divided in 3 compartments with 3 temp., heated and ventilated swing cabinet, mm 1200x700x900 h

**037.AC** - Cabinet heated trolley with separated basins (GN not included), structure completely made in stainless steel 18/10 AISI 304. Pressed no-drops basin divided in sections 1/1 GN H 200, double insulated wall and anti-drop board. Lower compartment closed by swing doors. Temperature of each compartment controlled by a digital thermostat 30° - 90° C°. Heating by electrical contact resistance 500W dry/bainmarie functioning 230 V 50/60 Hz. Cable spiral-shaped with CE plug and socket hook; push handle. 2 grey not marking rubber fixed wheels Ø 125 mm, 2 with brake, 4 bumpers made in black PVC. Capacity 4 GN1/1, Basin divided in 4 compartments with 4 temp., heated and ventilated swing cabinet, mm 1580x700x900 h