

Trolley



Heated trolley with pressed no-drops basin bain-marie and dry heating (GN not included). Welded frame made in stainless steel 18/10 AISI 304, square tube 30x30 mm. Pressed no-drops basin for GN h 200 mm, double and insulated wall. Temperature controlled by a digital thermostat 30°-90° C°. Spiral cable with CE plug and socket hook; push handle. Heating by electrical contact resistance functioning bain-marie and dry ways 230 V 50/60 Hz. 4 grey not marking rubber swivelling

Metaltecnica © Page 1 of 3

wheels Ø 125 mm, 2 with brake. 4 rubber bumpers made in black PVC. Bain-marie heated trolley 1650 W, capacity 2 GN 1/2 H 200 (40-50 dishes) mm 850x640x900 h - 026.AB/E

Dimension:

Length: 850.0 mm Depth: 640.0 mm Height: 900.0 mm Weight: 38.0 kg Volume: 0.49 mg

Packaging length: 1050.0 mm Packaging depth: 750.0 mm Packaging height: 1100.0 mm Packaging weight: 48.0 kg Packaging volume: 0.87 mq

Options:

Model:

O26.AC/E - Heated trolley with pressed no-drops basin bain-marie and dry heating (GN not included). Welded frame made in stainless steel 18/10 AISI 304, square tube 30x30 mm. Pressed no-drops basin for GN h 200 mm, double and insulated wall. Temperature controlled by a digital thermostat 30°-90° C°. Spiral cable with CE plug and socket hook; push handle. Heating by electrical contact resistance functioning bain-marie and dry ways 230 V 50/60 Hz. 4 grey not marking rubber swivelling wheels Ø 125 mm, 2 with brake. 4 rubber bumpers made in black PVC. Bain-marie heated trolley 1800 W, capacity 3 GN 1/2 H 200 (50 - 60 dishes) mm 1260x640x900 h

O26.AD/E - Heated trolley with pressed no-drops basin bain-marie and dry heating (GN not included). Welded frame made in stainless steel 18/10 AlSI 304, square tube 30x30 mm. Pressed no-drops basin for GN h 200 mm, double and insulated wall. Temperature controlled by a digital thermostat 30°-90° C°. Spiral cable with CE plug and socket hook; push handle. Heating by electrical contact resistance functioning bain-marie and dry ways 230 V 50/60 Hz. 4 grey not marking rubber swivelling wheels

Metaltecnica © Page 2 of 3

 \emptyset 125 mm, 2 with brake. 4 rubber bumpers made in black PVC. Bain-marie heated trolley 1900 W, capacity 4 GN 1/2 H 200 (60 - 80 dishes) mm 1580x640x900 h

Metaltecnica © Page 3 of 3