

## Trolley



Thermobox trolley heated version with hinged door, 0/+90°C, 900W, 230V, 50/60Hz, cap. 14xGN1/1 H40mm or 7xGN1/1 H100mm or 3xGN1/1 H200mm + 2xGN1/1 H40mm. Pitch mm.55. - TNG/14C

## **Dimension:**

Metaltecnica © Page 1 of 2

Length: 485.0 mm Depth: 805.0 mm Height: 1140.0 mm Weight: 70.0 kg Volume: 0.44 mq

Packaging length: 1050.0 mm Packaging depth: 750.0 mm Packaging height: 1340.0 mm Packaging weight: 80.0 kg Packaging volume: 1.05 mq

## **Options:**

## Model:

**TNG/11C** - Thermobox trolley heated version with hinged door, 0/+90°C, 900W, 230V, 50/60Hz, cap. 11xGN1/1 H40mm or 5xGN1/1 H100mm + 1xGN1/1 H40mm or 2xGN1/1 H200mm + 3xGN1/1 H40mm. Pitch mm.55.

**TNG/20C** - Thermobox trolley heated version with hinged door, 0/+90°C, 900W, 230V, 50/60Hz, cap. 20xGN1/1 H40mm or 10xGN1/1 H100mm or 5xGN1/1 H200mm. Pitch mm.55.

**TNG/9C** - Thermobox trolley heated version with hinged door, 0/+90°C, 900W, 230V, 50/60Hz, cap. 9xGNl/1 H40mm or 4xGNl/1 H100mm + 1xGNl/1 H40mm or 2xGNl/1 H200mm + 1xGNl/1 H40mm. Pitch mm.55.

Metaltecnica © Page 2 of 2