



METALTECNICA  
Italian catering equipment

---

## Trolley

---



Refrigerated cabinet trolley for plates. Carrying frame in stainless steel AISI304 18/10. Temp. +5°-+15°C. Cap. 80 plates max diam. 28-32 cm, arranged on 4 plastic rows. Solid base on 4 swivelling castors, 2 with brake; 4 push handles that permit a quicker service and an easy placement in any environment, from the dining room to the refrigerated cell without any problem. Static refrigerated condensing unit with 300W refrigerating gas 134A. Light switch. Temperature control through digital

thermostat, electric feeding 230V. In the inner compartment there is a condense-collecting basin, single opening, swivelling dish-holding grid - dim. 750x750x1900h mm - 346.RR

#### Dimension:

Length: 750.0 mm

Depth: 750.0 mm

Height: 1900.0 mm

Weight: 105.0 kg

Volume: 1.07 mq

Packaging length: 750.0 mm

Packaging depth: 750.0 mm

Packaging height: 2100.0 mm

Packaging weight: 115.0 kg

Packaging volume: 1.18 mq

#### Options:

##### Model:

**346.MR** - Refrigerated cabinet trolley for plates. Carrying frame in stainless steel AISI304 18/10. Temp. +5°-+15°C. Cap. 92 plates max diam. 28-32 cm, arranged on 4 plastic rows. Solid base on 4 swivelling castors, 2 with brake; 4 push handles that permit a quicker service and an easy placement in any environment, from the dining room to the refrigerated cell without any problem. Static refrigerated condensing unit with 300W refrigerating gas 134A. Light switch. Temperature control through digital thermostat, electric feeding 230V. In the inner compartment there is a condense-collecting basin, double opening, fixed dish-holding grid - dim. 650x650x1900h mm